SAFETY DATA SHEET

Lukas Rectified Balsam Turpentine

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name

Lukas Rectified Balsam Turpentine

Product no.

K2211xxxx

▼UK REACH registration number

01-2119502456-45-XXXX

Other means of identification

Index No.: 650-002-00-6
EC No.: 232-350-7
CAS No.: 8006-64-2

Unique formula identifier (UFI)

14M8-9QTD-S12V-0FJS

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Art supplies and hobby preparations

Use descriptors (UK REACH)

Sectors of use	**Description**
LCS "C"	Consumer uses: Private households (= general public = consumers)
Product category	**Description**
PC 9a	Coatings and Paints, Fillers, Putties, Thinners
Process category	**Description**
PROC 10	Roller application or brushing

Uses advised against

None known.

1.3. Details of the supplier of the safety data sheet

Company and address

F.I.L.A. S.p.A.
Via XXV Aprile, 5
PERO
20016 Milan
+390238105291
Lukas.eu

Revision

13/07/2026

SDS Version

2.0

Date of previous version

26/02/2025 (1.0)

1.4. ▼Emergency telephone number

Healthcare professionals: Dial 0344 892 0111 to reach The National Poisons Information Service (NPIS) (24 hour service)
General public:

England - Dial 111 to reach NHS 111 (24 hour service)
Scotland - Dial 111 to reach NHS 24 (24 hour service)
Wales - Dial 111 or 0845 4647 to reach NHS Direct (24 hour service)
See section 4 “First aid measures”.

SECTION 2: Hazards identification

Classified according to Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.

2.1. Classification of the substance or mixture

Flam. Liq. 3; H226, Flammable liquid and vapour.
Acute Tox. 4; H302, Harmful if swallowed.
Asp. Tox. 1; H304, May be fatal if swallowed and enters airways.
Acute Tox. 4; H312, Harmful in contact with skin.
Skin Irrit. 2; H315, Causes skin irritation.
Skin Sens. 1; H317, May cause an allergic skin reaction.
Eye Irrit. 2; H319, Causes serious eye irritation.
Acute Tox. 4; H332, Harmful if inhaled.
Aquatic Chronic 2; H411, Toxic to aquatic life with long lasting effects.

2.2. Label elements

Hazard pictogram(s)

Signal word

Danger

Hazard statement(s)

Flammable liquid and vapour. (H226)
Harmful if swallowed, in contact with skin or if inhaled. (H302+H312+H332)
May be fatal if swallowed and enters airways. (H304)
Causes skin irritation. (H315)
May cause an allergic skin reaction. (H317)
Causes serious eye irritation. (H319)
Toxic to aquatic life with long lasting effects. (H411)

Precautionary statement(s)

General

If medical advice is needed, have product container or label at hand. (P101)
Keep out of reach of children. (P102)

Prevention

Avoid breathing mist/vapour. (P261)
Wear eye protection/protective gloves/protective clothing. (P280)

Response

IF SWALLOWED: Immediately call a POISON CENTER/doctor. (P301+P310)
Do NOT induce vomiting. (P331)

Storage

Store locked up. (P405)

▼Disposal

Dispose of contents/container in accordance with local regulation. (P501)

Hazardous substances

turpentine, oil

Additional labelling

UFI: 14M8-9QTD-S12V-0FJS

2.3. Other hazards

Additional warnings

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification. This product does not contain any substances considered to be endocrine disruptors in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2023/707.

SECTION 3: Composition/information on ingredients

3.1. ▼Substances

Product/substance	Identifiers	% w/w	Classification	Note
turpentine, oil	CAS No.: 8006-64-2 EC No.: 232-350-7 UK-REACH: 01-2119502456-45-XXXX Index No.: 650-002-00-6	95-100%	Flam. Liq. 3, H226 Acute Tox. 4, H302 Asp. Tox. 1, H304 Acute Tox. 4, H312 Skin Irrit. 2, H315 Skin Sens. 1, H317 Eye Irrit. 2, H319 Acute Tox. 4, H332 Aquatic Chronic 2, H411	[19]

3.2. Mixtures

Not applicable. This product is a substance.

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

[19] UVCB = Unknown or variable composition, complex reaction products or of biological materials

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the injured person into fresh air. Make sure the injured person is continuously monitored. Prevent shock by keeping the injured person warm and calm. If breathing ceases, give mouth-to-mouth resuscitation. If unconscious, roll the injured person into recovery position. Call an ambulance.

Skin contact

Remove contaminated clothing and shoes immediately. Ensure to wash exposed skin thoroughly with water and soap. Skin cleanser can be used. DO NOT use solvents or thinners.
If skin irritation occurs: Get medical advice/attention.

Eye contact

If in eyes: Flush eyes immediately with plenty of water or isotonic water (20-30 °C) for at least 5 minutes and continue until irritation stops. Remove contact lenses. Make sure to flush under upper and lower eyelids. If irritation continues, contact a doctor. Continue flushing during transport.

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER/doctor.
Do not induce vomiting! If vomiting occurs, keep head facing down so that vomit does not get into the lungs. Call a doctor or ambulance. Symptoms of chemical pneumonia can appear after several hours. People who have swallowed the product should therefore be kept under medical attention for at least 48 hours.

Burns

Rinse with water until pain stops then continue to rinse for 30 minutes.

4.2. Most important symptoms and effects, both acute and delayed

This product contains substances that can cause chemical pneumonia if swallowed. Symptoms of chemical pneumonia may appear after several hours.
Sensitisation: This product contains substances, which may trigger allergic reaction upon dermal contact. Manifestation of allergic reactions typically takes place within 12-72 hours after exposure.
Neurotoxic effects: This product contains organic solvents, which may cause adverse effects to the nervous system. Symptoms of neurotoxicity include: loss of appetite, headache, dizziness, ringing in ears, tingling sensations of skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer and may result in an increased absorption potential of other hazardous substances at the area of exposure.

4.3. Indication of any immediate medical attention and special treatment needed

IF exposed or concerned:
Get immediate medical advice/attention.

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.
Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

Flammable liquid and vapour.
In use may form flammable/explosive vapour-air mixture.
Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

5.3. ▼Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.
Hazchem Code: 3Y

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Storages not yet ignited must be cooled by water mist. Remove flammable materials if conditions allow it. Ensure sufficient ventilation.
Avoid direct contact with spilled substances.
Ensure adequate ventilation, especially in confined areas.
Avoid inhalation of vapours from spilled material.
Contaminated areas may be slippery.

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc. In the event of leakage to the surroundings, contact local environmental authorities.

6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.
Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections

See section 13 “Disposal considerations” on handling of waste.
See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: Handling and storage

7.1. ▼Precautions for safe handling

Ground and bond container and receiving equipment.

Use explosion-proof electrical/lighting/ventilating equipment.
Use non-sparking tools.
Take action to prevent static discharges.
It is recommended to install waste collection trays in order to prevent emissions to the waste water system and surrounding environment.
Avoid direct contact with the product.
Avoid contact during pregnancy and while nursing.
Smoking, drinking and consumption of food is not allowed in the work area.
See section 8 "Exposure controls/personal protection" for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.
Take action to prevent static discharges.
Must be stored in a cool and well-ventilated area, away from possible sources of ignition.

Recommended storage material

Always store in containers of the same material as the original container.

Storage conditions

Dry, cool and well ventilated
Room temperature 15 to 25°C

Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

turpentine, oil
Long term exposure limit (8 hours) (ppm): 100
Long term exposure limit (8 hours) (mg/m^3): 566
Short term exposure limit (15 minutes) (ppm): 150
Short term exposure limit (15 minutes) (mg/m^3): 850

The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677 The Stationery Office 2002.
EH40/2005 Workplace exposure limits (Fourth Edition 2020).

DNEL

No data available.

PNEC

No data available.

8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

Exposure scenarios

There are no exposure scenarios implemented for this product.

Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

Appropriate technical measures

The formation of vapours must be kept at a minimum and below current limit values (see above). Installation of a local exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure eyewash and emergency showers are clearly marked.
Apply standard precautions during use of the product. Avoid inhalation of vapours.

Hygiene measures

Take off contaminated clothing and wash it before reuse.

Measures to avoid environmental exposure

Keep damming materials near the workplace. If possible, collect spillage during work.

Individual protection measures, such as personal protective equipment

Generally

Use only UKCA marked protective equipment.

Respiratory Equipment

Type	Class	Colour	Standards
Respiratory protection is not needed in the event of adequate ventilation.			

Skin protection

Recommended	Type/Category	Standards	
Wear appropriate protection clothing, e.g. coveralls in polypropylene or working clothes in cotton or polyester.	-	-	

▼Hand protection

Material	Glove thickness (mm)	Breakthrough time (min.)	Standards	
Nitrile	2,0	> 480	EN374-2, EN16523-1, EN388, EN407	

▼Eye protection

Type	Standards	
Safety glasses with side shields.	EN 166 / EN ISO 16321-1	

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state

Liquid

Colour

Clear

Odour / Odour threshold

No data available.

pH

No data available.

Density (g/cm^3)

0.87

Kinematic viscosity

1.3 mPa.s (20 °C)

Particle characteristics

Does not apply to liquids.

Phase changes

Melting point/Freezing point (°C)

No data available.

Softening point/range (°C)

Does not apply to liquids.

Boiling point (°C)
154
Vapour pressure
519 Pa (20 °C)
Relative vapour density
No data available.
Decomposition temperature (°C)
No data available.

Data on fire and explosion hazards

Flash point (°C)
34
Flammability (°C)
The material is ignitable.
Auto-ignition temperature (°C)
255
Lower and upper explosion limit (% v/v)
0.7 - 6.1

Solubility

Solubility in water
Insoluble
n-octanol/water coefficient (LogKow)
No data available.
Solubility in fat (g/L)
No data available.

9.2. Other information

VOC (g/l)
860
Oxidizing properties
No data available.
Other physical and chemical parameters
No data available.

SECTION 10: Stability and reactivity

10.1. Reactivity
No data available.
10.2. Chemical stability
The product is stable under the conditions, noted in section 7 “Handling and storage”.
10.3. Possibility of hazardous reactions
None known.
10.4. Conditions to avoid
Avoid static electricity.
Do not expose to any forms of heat (e.g. solar radiation). May lead to excess pressure.
10.5. Incompatible materials
Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.
10.6. Hazardous decomposition products
Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008 as retained and amended in UK law

Acute toxicity
Harmful if swallowed.
Harmful in contact with skin.

Harmful if inhaled.

Skin corrosion/irritation
Causes skin irritation.

Serious eye damage/irritation
Causes serious eye irritation.

Respiratory sensitisation
Based on available data, the classification criteria are not met.

Skin sensitisation
May cause an allergic skin reaction.

Germ cell mutagenicity
Based on available data, the classification criteria are not met.

Carcinogenicity
Based on available data, the classification criteria are not met.

Reproductive toxicity
Based on available data, the classification criteria are not met.

STOT-single exposure
Based on available data, the classification criteria are not met.

STOT-repeated exposure
Based on available data, the classification criteria are not met.

Aspiration hazard
May be fatal if swallowed and enters airways.

▼Symptoms related to the physical, chemical and toxicological characteristics
Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.
Neurotoxic effects: This product contains organic solvents, which may cause adverse effects to the nervous system. Symptoms of neurotoxicity include: loss of appetite, headache, dizziness, ringing in ears, tingling sensations of skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer and may result in an increased absorption potential of other hazardous substances at the area of exposure.

11.2. Information on other hazards

Endocrine disrupting properties
This mixture/product does not contain any substances known to have hormone-disrupting properties in relation to health.

Other information
None known.

SECTION 12: Ecological information

12.1. Toxicity
Toxic to aquatic life with long lasting effects.

12.2. Persistence and degradability
Based on available data, the classification criteria are not met.

12.3. Bioaccumulative potential
Based on available data, the classification criteria are not met.

12.4. Mobility in soil
No data available.

12.5. Results of PBT and vPvB assessment
This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

12.6. Endocrine disrupting properties
This mixture/product does not contain any substances considered to have endocrine-disrupting properties in relation to the environment.

12.7. Other adverse effects
This product contains substances that are toxic to the environment. May result in adverse effects to aquatic organisms.
This product contains substances, which may cause adverse long-term effects to the aquatic environment.

SECTION 13: Disposal considerations

Waste treatment methods

Product is covered by the regulations on hazardous waste. (*)
HP 3 - Flammable
HP 4 - Irritant (skin irritation and eye damage)
HP 5 - Specific Target Organ Toxicity (STOT)/Aspiration Toxicity
HP 6 - Acute toxicity
HP 13 – Sensitising
HP 14 – Ecotoxic
Dispose of contents/container to an approved waste disposal plant.
Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.

EWC code

08 01 11* Waste paint and varnish containing organic solvents or other dangerous substances

Specific labelling

Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: Transport information

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information:
ADR/A DN/RID	UN1299	TURPENTINE	Transport hazard class: 3 Label: 3 Classification code: F1 	III	Yes	Limited quantities: 5 L Tunnel restriction code: (D/E) See below for additional information.
IMDG	UN1299	TURPENTINE	Transport hazard class: 3 Label: 3 Classification code: F1 	III	Yes	Limited quantities: 5 L EmS: F-E S-E See below for additional information.
IATA	UN1299	TURPENTINE	Transport hazard class: 3 Label: 3 Classification code: F1 	III	Yes	See below for additional information.

* Packing group
** Environmental hazards

▼Additional information

This product is within scope of the regulations of transport of dangerous goods.

ADR/ADN/RID / See Table A, section 3.2.1 for any information on special provisions, requirements, or warnings in connection with transport. See section 5.4.3, for instructions in writing regarding mitigation of damages in relation to incidents or accidents during transport.
IMDG / See section 3.2.1, for any information on special provisions, requirements, or warnings in connection with transport.
IATA / See Table 4.2 for any information on special provisions, requirements, or warnings in connection with transport.
Hazchem Code: 3Y

14.6. Special precautions for user

Not applicable.

14.7. Maritime transport in bulk according to IMO instruments

No data available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application

People under the age of 18 shall not be exposed to this product.
Pregnant women and women breastfeeding must not be exposed to this product. The risk, and possible technical precautions or design of the workplace needed to eliminate exposure, must be considered.

Demands for specific education

No specific requirements.

Control of Major Accident Hazards (COMAH) - Categories / dangerous substances

P5c - FLAMMABLE LIQUIDS, Qualifying quantity (lower-tier): 5.000 tonnes / (upper-tier): 50.000 tonnes
E2 - ENVIRONMENTAL HAZARDS, Qualifying quantity (lower-tier): 200 tonnes / (upper-tier): 500 tonnes

UK-REACH, Annex XVII

turpentine, oil is subject to UK-REACH restrictions (entry 40).

Additional information

Tactile warning.
If this product is sold in retail, it must be delivered with child-resistant fastening.

Sources

The Management of Health and Safety at Work Regulations 1999.
The Health and Safety at Work etc. Act 1974 Regulations 2013.
Control of Major Accident Hazards (COMAH) Regulations 2015.
Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.
Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures (CLP) as retained and amended in UK law.
Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) as retained and amended in UK law.

15.2. Chemical safety assessment

No

SECTION 16: Other information

Full text of H-phrases as mentioned in section 3

H226, Flammable liquid and vapour.
H302, Harmful if swallowed.
H304, May be fatal if swallowed and enters airways.
H312, Harmful in contact with skin.
H315, Causes skin irritation.
H317, May cause an allergic skin reaction.
H319, Causes serious eye irritation.
H332, Harmful if inhaled.
H411, Toxic to aquatic life with long lasting effects.

The full text of identified uses as mentioned in section 1

LCS "C" = Consumer uses: Private households (= general public = consumers)
PROC 10 = Roller application or brushing

PC 9a = Coatings and Paints, Fillers, Putties, Thinners

▼Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway
ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor
CAS = Chemical Abstracts Service
CE = Conformité Européenne (European conformity)
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
CSA = Chemical Safety Assessment
CSR = Chemical Safety Report
DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level
EC = Effective concentration
ED = Effective dose
EINECS = European Inventory of Existing Commercial chemical Substances
EL = Effective Loading
ErC = Concentration associated with x% growth rate response
ES = Exposure Scenario
EUH statement = CLP-specific Hazard statement
EuPCS = European Product Categorisation System
EWC = European Waste Catalogue
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
GWP = Global warming potential
HP = Hazardous Property code
IARC = International Agency for Research on Cancer (IARC)
IATA = International Air Transport Association
IBC = Intermediate Bulk Container
IC = X maximum inhibitory concentration
IMDG = International Maritime Dangerous Goods
LC = Lethal concentration
LCLo = Value is the lowest concentration of a material in air reported to have caused the death of animals or humans
LD = Lethal dose
LOAEC = Lowest Observed Adverse Effect Concentration
LOAEL = Lowest Observed Adverse Effect Level
LOEC = Lowest Observed Effect Concentration
LogKow = logarithm of the n-octanol/water coefficient
LL = Lethal Loading
M = For multiplication factor
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
NOAEC = No Observed Adverse Effect Concentration
NOAEL = No Observed Adverse Effect Level
NOEC = No Observed Effect Concentration
NOELR = No Observable Effect Loading Rate
OECD = Organisation for Economic Co-operation and Development
PBT = Persistent, Bioaccumulative and Toxic
PNEC = Predicted No Effect Concentration
RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail
RRN = REACH Registration Number
SCL = A specific concentration limit
SVHC = Substances of Very High Concern
STOT-RE = Specific Target Organ Toxicity - Repeated Exposure
STOT-SE = Specific Target Organ Toxicity - Single Exposure
TWA = Time weighted average
UN = United Nations
UVBC = Unknown or variable composition, complex reaction products or of biological materials

VOC = Volatile Organic Compound
vPvB = Very Persistent and Very Bioaccumulative

Additional information

The classification of the substance/mixture in regard of health hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.
The classification of the substance/mixture in regard of environmental hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.
The classification of the mixture in regard to physical hazards has been based on experimental data.

The safety data sheet is validated by

AS

Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a triangle.
The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.
It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.
Country-language: GB-en