Safety data sheet
according to UK REACH

Printing date 10.07.2026 Version number 7 (replaces version 6) Revision: 10.07.2026

*
SECTION 1: Identification of the substance/mixture and of the company/undertaking

· **1.1 Product identifier**

· **Trade name: STUDIO Acryl Firnis seidenmatt**

· **Article number:** 169212
· **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
· **Sector of Use**
SU21 Consumer uses: Private households / general public / consumers
SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
· **Product category** PC9a Coatings and paints, thinners, paint removers
· **Process category**
PROC11 Non industrial spraying
PROC7 Industrial spraying
· **Application of the substance / the mixture** Lacquer

· **1.3 Details of the supplier of the safety data sheet**
· **Manufacturer/Supplier:**
Daler-Rowney Ltd.
Bracknell, Berkshire
RG12 8SS
United Kingdom
Telephone: +44 (0) 1344 461083
Telefax: +44 (0) 1344 486511
email: info@daler-rowney.com

· **Further information obtainable from:** Department Product Safety
· **1.4 Emergency telephone number:** +44 (0) 1344 461083

*
SECTION 2: Hazards identification

· **2.1 Classification of the substance or mixture**
· **Classification according to Regulation (EC) No 1272/2008**

GHS02 flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

GHS05 corrosion

Eye Dam. 1 H318 Causes serious eye damage.

GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

GHS07

Acute Tox. 4 H302 Harmful if swallowed.
Skin Irrit. 2 H315 Causes skin irritation.
STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

(Contd. on page 2)

Safety data sheet
according to UK REACH

Printing date 10.07.2026 Version number 7 (replaces version 6) Revision: 10.07.2026

Trade name: STUDIO Acryl Firnis seidenmatt

(Contd. of page 1)

· **2.2 Label elements**
· **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the GB CLP regulation.
· **Hazard pictograms**

GHS02 GHS05 GHS07 GHS09

· **Signal word** Danger

· **Hazard-determining components of labelling:**
butan-1-ol
Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics
Hydrocarbons, C6-C7, Isoalkane, Cyclics, <5%n-Hexane
Hydrocarbons, C9-C10, n-alkanes, iso-alkanes, cyclics, <2% aromatics
· **Hazard statements**
H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.
H302 Harmful if swallowed.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.
· **Precautionary statements**
P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P260 Do not breathe spray.
P280 Wear eye protection / face protection.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER/doctor.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501 Dispose of contents / container in accordance with regional regulations.
· **Additional information:**
Buildup of explosive mixtures possible without sufficient ventilation.
· **2.3 Other hazards**
· **Results of PBT and vPvB assessment**
· **PBT:** Not applicable
· **vPvB:** Not applicable

*
SECTION 3: Composition/information on ingredients

· **3.2 Mixtures**
· **Description:** Mixture of substances listed below with nonhazardous additions.

(Contd. on page 3)

Safety data sheet
according to UK REACH

Printing date 10.07.2026 Version number 7 (replaces version 6) Revision: 10.07.2026

Trade name: STUDIO Acryl Firnis seidenmatt

(Contd. of page 2)

· **Dangerous components:**

CAS: 115-10-6 EINECS: 204-065-8 Index number: 603-019-00-8 Reg.nr.: 01-2119472128-37	dimethyl ether Flam. Gas 1A, H220 Press. Gas (Comp.), H280	25-<50%
CAS: 71-36-3 EINECS: 200-751-6 Index number: 603-004-00-6 Reg.nr.: 01-2119484630-38	butan-1-ol Flam. Liq. 3, H226 Eye Dam. 1, H318 Acute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335-H336	20-<25%
EC number: 920-750-0 Reg.nr.: 01-2119473851-33-xxxx	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics Flam. Liq. 2, H225 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 STOT SE 3, H336 EUH066	12.5-<20%
EC number: 926-605-8 Reg.nr.: 01-2119486291-36	Hydrocarbons, C6-C7, Isoalkane, Cyclics, <5%n-Hexane Consisting of: 110-54-3 n-hexane (2%) Flam. Liq. 2, H225 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 STOT SE 3, H336	5-<10%
EC number: 927-241-2 Reg.nr.: 01-2119471843-32	Hydrocarbons, C9-C10, n-alkanes, iso-alkanes, cyclics, <2% aromatics Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H336 Aquatic Chronic 3, H412 EUH066	5-<10%

· **Additional information:**
The content of Benzene (EINECS-Nr. 200-753-7) in the ingredients is less than 0,1% (Note P Annex 1A 1272/2008 EU), so the classification as carcinogen need not to apply.
In accordance with the current Annex II of UK REACH, the concentration of the substances contained in the mixture are specified. For the classification of aerosols, the values used for calculation may differ.
This product contains n-hexane (CAS 110-54-3) above the 0.1% (w/w) threshold. n-Hexane is not intentionally added as a substance to the formulation; its presence is due to it being an impurity from one of the substances used during manufacturing. Inclusion on the SVHC Candidate List is due to the inherent properties of n-hexane as a substance; however, at the concentration found in the substance used in our product, it does not meet the criteria for classification as a CMR (Carcinogenic, Mutagenic, or Reproductive toxicant) substance (see table in this section).
For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· **4.1 Description of first aid measures**
· **General information:**
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
· **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
· **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
· **After swallowing:**
Call for a doctor immediately.
Drink plenty of water and provide fresh air. Call for a doctor immediately.
· **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

(Contd. on page 4)

Safety data sheet
according to UK REACH

Trade name: STUDIO Acryl Firnis seidenmatt

(Contd. of page 3)

· **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

· **5.1 Extinguishing media**
· **Suitable extinguishing agents:**
CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
Use fire extinguishing methods suitable to surrounding conditions.
· **5.2 Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
· **5.3 Advice for firefighters** -
· **Protective equipment:** Mouth respiratory protective device.

SECTION 6: Accidental release measures

· **6.1 Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
Keep away from ignition sources.
· **6.2 Environmental precautions:**
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
· **6.3 Methods and material for containment and cleaning up:**
Use neutralising agent.
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
· **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

*
SECTION 7: Handling and storage

· **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.
· **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Keep respiratory protective device available.

· **7.2 Conditions for safe storage, including any incompatibilities**
· **Storage:**
· **Requirements to be met by storerooms and receptacles:**
Observe official regulations on storing packagings with pressurised containers.
· **Information about storage in one common storage facility:** Not required
· **Further information about storage conditions:** Keep container tightly sealed.
· **Storage class:** 2 B
· **7.3 Specific end use(s)** No further relevant information available.

*
SECTION 8: Exposure controls/personal protection

· **8.1 Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**	
115-10-6 dimethyl ether	
WEL	Short-term value: 958 mg/m³, 500 ppm Long-term value: 766 mg/m³, 400 ppm

(Contd. on page 5)

Safety data sheet
according to UK REACH

Printing date 10.07.2026 Version number 7 (replaces version 6) Revision: 10.07.2026

Trade name: STUDIO Acryl Firnis seidenmatt

(Contd. of page 4)

71-36-3 butan-1-ol	
WEL	Short-term value: 154 mg/m³, 50 ppm Sk

· **DNELs**

71-36-3 butan-1-ol		
Oral	DNEL	3.125 mg/kg (Consumer, longterm systemic)
Inhalative	DNEL	310 mg/m3 (Worker, longterm local)
	DNEL	55 mg/m3 (Consumer, longterm local)
Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics		
Dermal	DNEL	773 mg/kg /per day (Worker, longterm systemic)
Inhalative	DNEL	2035 mg/m3 (Worker, longterm systemic)
Hydrocarbons, C6-C7, Isoalkane, Cyclics, <5%n-Hexane		
Oral	DNEL	1301 mg/kg /per day (Consumer, longterm systemic)
Dermal	DNEL	13964 mg/kg /per day (Worker, longterm systemic)
	DNEL	1377 mg/kg /per day (Consumer, longterm systemic)
Inhalative	DNEL	5306 mg/m3 (Worker, longterm systemic)
	DNEL	1131 mg/m3 (Consumer, longterm systemic)
Hydrocarbons, C9-C10, n-alkanes, iso-alkanes, cyclics, <2% aromatics		
Oral	DNEL	46 mg/kg /per day (Consumer, longterm systemic)
Dermal	DNEL	77 mg/kg /per day (Worker, longterm systemic)
	DNEL	46 mg/kg /per day (Consumer, longterm systemic)
Inhalative	DNEL	871 mg/m3 (Worker, longterm systemic)
	DNEL	185 mg/m3 (Consumer, longterm systemic)

· **PNECs**

71-36-3 butan-1-ol	
PNEC	0.082 mg/l (Freshwater)
PNEC	0.0082 mg/l (Seawater)
PNEC	2.25 mg/l (Sporadic release)
PNEC	2476 mg/l (Sewage treatment plant)
PNEC	0.178 mg/kg (Freshwater sediment)
PNEC	0.0178 mg/kg (Seawater sediment)
PNEC	0.015 mg/kg (Soil)

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**
· **Appropriate engineering controls** No further data; see section 7.
· **Individual protection measures, such as personal protective equipment**
· **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.
Avoid contact with the skin.
Avoid contact with the eyes and skin.
Avoid contact with the eyes.
· **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

(Contd. on page 6)

Safety data sheet
according to UK REACH

Trade name: STUDIO Acryl Firnis seidenmatt

(Contd. of page 5)

Filter A2/P3

· **Hand protection**

Protective gloves

· **Material of gloves**
Butyl rubber, BR
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· **Penetration time of glove material**
Butyl rubber gloves with a thickness of 0.4 mm are resistant to:
Acetone: 480 min
Butyl acetate: 60 min
Ethyl acetate: 170 min
Xylene: 42 min
Butyl rubber gloves with a thickness of 0.4 mm are solvent resistant for 42- 480 minutes. As protective measure, we recommend that users and responsible persons for work safety assume solvent resistance length of 42 minutes. Considering the data in section 3 of this SDS, one can assume longer resistance length in particular cases.

· **Eye/face protection**

Tightly sealed goggles

*
SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**	
· **General Information**	
· **Physical state**	Aerosol
· **Colour:**	Clear
· **Odour:**	Characteristic
· **Odour threshold:**	Not determined
· **Melting point/freezing point:**	Undetermined
· **Boiling point or initial boiling point and boiling range**	Not applicable, as aerosol
· **Flammability**	Not applicable
· **Lower and upper explosion limit**	
· **Lower:**	1.5 Vol % (71-36-3 butan-1-ol)
· **Upper:**	26.2 Vol % (115-10-6 dimethyl ether)
· **Flash point:**	Not applicable, as aerosol
· **Auto-ignition temperature:**	200 °C (392 °F) (Hydrocarbons, C9-C10, n-alkanes, iso-alkanes, cyclics, <2% aromatics)
· **Decomposition temperature:**	Not determined
· **pH**	Mixture is non-soluble (in water).
· **Viscosity:**	
· **Kinematic viscosity**	Not determined
· **Dynamic:**	Not determined
· **Solubility**	
· **water:**	Not miscible or difficult to mix.
· **Partition coefficient n-octanol/water (log value)**	Not determined
· **Vapour pressure at 20 °C (68 °F):**	4000 hPa (3000.2 mm Hg) (115-10-6 dimethyl ether)
· **Vapour pressure at 50 °C (122 °F):**	11400 hPa (8550.7 mm Hg)
· **Density and/or relative density**	
· **Density at 20 °C (68 °F):**	0.7 g/cm³ (5.8 lbs/gal)

(Contd. on page 7)

Safety data sheet
according to UK REACH

Printing date 10.07.2026 Version number 7 (replaces version 6) Revision: 10.07.2026

Trade name: STUDIO Acryl Firnis seidenmatt

(Contd. of page 6)

· **Relative density**	Not determined
· **Vapour density**	Not determined
· **9.2 Other information**	
· **Appearance:**	
· **Form:**	Aerosol
· **Important information on protection of health and environment, and on safety.**	
· **Explosive properties:**	Not determined
· **Solvent content:**	
· **Organic solvents:**	95.8 %
· **VOC (EC)**	--- 700.0 g/l
· **VOC-EU%**	95.00 %
· **Solids content:**	4.1 %
· **Change in condition**	
· **Evaporation rate**	Not applicable.
· **Information with regard to physical hazard classes**	
· **Explosives**	Void
· **Flammable gases**	Void
· **Aerosols**	Extremely flammable aerosol. Pressurised container: May burst if heated.
· **Oxidising gases**	Void
· **Gases under pressure**	Void
· **Flammable liquids**	Void
· **Flammable solids**	Void
· **Self-reactive substances and mixtures**	Void
· **Pyrophoric liquids**	Void
· **Pyrophoric solids**	Void
· **Self-heating substances and mixtures**	Void
· **Substances and mixtures, which emit flammable gases in contact with water**	Void
· **Oxidising liquids**	Void
· **Oxidising solids**	Void
· **Organic peroxides**	Void
· **Corrosive to metals**	Void
· **Desensitised explosives**	Void

SECTION 10: Stability and reactivity

· **10.1 Reactivity** No further relevant information available.
· **10.2 Chemical stability**
· **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
· **10.3 Possibility of hazardous reactions** No dangerous reactions known.
· **10.4 Conditions to avoid** No further relevant information available.
· **10.5 Incompatible materials:** No further relevant information available.
· **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

*

SECTION 11: Toxicological information

· **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
· **Acute toxicity** Harmful if swallowed.

· **LD/LC50 values relevant for classification:**		
71-36-3 butan-1-ol		
Oral	LD50	2292 mg/kg (rat)

(Contd. on page 8)

Safety data sheet
according to UK REACH

Printing date 10.07.2026 *Version number 7 (replaces version 6)* *Revision: 10.07.2026*

Trade name: STUDIO Acryl Firnis seidenmatt

(Contd. of page 7)

Dermal	*LD50*	*3430 mg/kg (rabbit)*
Inhalative	*LC50 / 4 h*	*17000 mg/m3 (rat)*
Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics		
Oral	*LD50*	*>5000 mg/kg (rat)*
Dermal	*LD50*	*>2000 mg/kg (rat)*
Inhalative	*LC50 / 4 h*	*>20000 mg/m3 (rat)*
Hydrocarbons, C6-C7, Isoalkane, Cyclics, <5%n-Hexane		
Oral	*LD50*	*>5000 mg/kg (rat)*
Dermal	*LD50*	*>2000 mg/kg (rat)*
Inhalative	*LC50 / 4 h*	*>20 mg/m3 (rat)*
Hydrocarbons, C9-C10, n-alkanes, iso-alkanes, cyclics, <2% aromatics		
Oral	*LD50*	*>15000 mg/kg (rat) (OECD 401)*
Dermal	*LD50*	*>3160 mg/kg (rabbit) (OECD 402)*
Inhalative	*LC50 / 4 h*	*>6100 mg/m3 (rat) (OECD 403)*

· ***Primary irritant effect:***
· ***Skin corrosion/irritation*** *Causes skin irritation.*
· ***Serious eye damage/irritation*** *Causes serious eye damage.*
· ***Respiratory or skin sensitisation*** *No sensitising effects known.*
· ***STOT-single exposure*** *May cause respiratory irritation. May cause drowsiness or dizziness.*
· ***11.2 Information on other hazards***

· ***Endocrine disrupting properties***
None of the ingredients is listed.

SECTION 12: Ecological information

· ***12.1 Toxicity***

· ***Aquatic toxicity:***	
115-10-6 dimethyl ether	
EC50 / 96 h	*155 mg/l (algae)*
LC50 / 48 h	*>4000 mg/l (daphnia magna)*
LC50 / 96 h	*>4000 mg/l (fish)*
71-36-3 butan-1-ol	
LC50 / 96 h	*1376 mg/l (fish)*
Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics	
EC50	*50 mg/l (algae)*
	5 mg/l (fish)
Hydrocarbons, C6-C7, Isoalkane, Cyclics, <5%n-Hexane	
EC50 / 48 h	*3 mg/l (daphnia magna / Wasserfloh)*
EC50 / 72 h	*30 mg/l (Pseudokirchneriella subcapitata)*
LC50 / 96 h	*11.4 mg/l (oncorhynchus mykiss)*

· ***12.2 Persistence and degradability*** *No further relevant information available.*
· ***12.3 Bioaccumulative potential*** *No further relevant information available.*
· ***12.4 Mobility in soil*** *No further relevant information available.*
· ***12.5 Results of PBT and vPvB assessment***
· ***PBT:*** *Not applicable*
· ***vPvB:*** *Not applicable*
· ***12.6 Endocrine disrupting properties***
The product does not contain substances with endocrine disrupting properties.

(Contd. on page 9)

Safety data sheet
according to UK REACH

Trade name: STUDIO Acryl Firnis seidenmatt

(Contd. of page 8)

· **12.7 Other adverse effects**
· **Remark:** Toxic for fish
· **Additional ecological information:**
· **General notes:**
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Must not reach sewage water or drainage ditch undiluted or unneutralised.
Danger to drinking water if even small quantities leak into the ground.
Also poisonous for fish and plankton in water bodies.
Toxic for aquatic organisms

*
SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**
· **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packaging:**
· **Recommendation:** Disposal must be made according to official regulations.

*
SECTION 14: Transport information

· **14.1 UN number or ID number**	
· **ADR, IMDG, IATA**	UN1950
· **14.2 UN proper shipping name**	
· **ADR**	1950 AEROSOLS, MARINE POLLUTANT/ ENVIRONMENTALLY HAZARDOUS
· **IMDG**	AEROSOLS, MARINE POLLUTANT
· **IATA**	AEROSOLS, flammable
· **14.3 Transport hazard class(es)**	
· **ADR**	
· **Class**	2 5F Gases.
· **Label**	2.1
· **IMDG**	
· **Class**	2.1 Gases.
· **Label**	2.1
· **IATA**	
· **Class**	2.1 Gases.
· **Label**	2.1

(Contd. on page 10)

Safety data sheet
according to UK REACH

Trade name: STUDIO Acryl Firnis seidenmatt

(Contd. of page 9)

· **14.4 Packing group**	
· **ADR, IMDG, IATA**	not regulated
· **14.5 Environmental hazards:**	
· **Marine pollutant:**	Yes Symbol (fish and tree)
· **Special marking (ADR):**	Symbol (fish and tree)
· **14.6 Special precautions for user**	Warning: Gases.
· **Hazard identification number (Kemler code):**	-
· **EMS Number:**	F-D,S-U
· **Stowage Code**	SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
· **Segregation Code**	SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
· **14.7 Maritime transport in bulk according to IMO instruments**	Not applicable
· **Transport/Additional information:**	
· **ADR**	
· **Limited quantities (LQ)**	1L
· **Excepted quantities (EQ)**	Code: E0 Not permitted as Excepted Quantity
· **Transport category**	2
· **Tunnel restriction code**	D
· **IMDG**	
· **Limited quantities (LQ)**	1L
· **Excepted quantities (EQ)**	Code: E0 Not permitted as Excepted Quantity
· **UN "Model Regulation":**	UN 1950 AEROSOLS, 2.1, MARINE POLLUTANT/ ENVIRONMENTALLY HAZARDOUS

*

SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
· **Poisons Act**

· **Regulated explosives precursors**
None of the ingredients is listed.

· **Regulated poisons**
None of the ingredients is listed.

· **Reportable explosives precursors**
None of the ingredients is listed.

· **Reportable poisons**
None of the ingredients is listed.

(Contd. on page 11)

Safety data sheet
according to UK REACH

Trade name: STUDIO Acryl Firnis seidenmatt

(Contd. of page 10)

· ***Directive 2012/18/EU***
· ***Named dangerous substances - ANNEX I*** *None of the ingredients is listed.*
· ***Seveso category***
P3a FLAMMABLE AEROSOLS
E2 Hazardous to the Aquatic Environment
· ***Qualifying quantity (tonnes) for the application of lower-tier requirements*** *150 t*
· ***Qualifying quantity (tonnes) for the application of upper-tier requirements*** *500 t*
· ***15.2 Chemical safety assessment:*** *A Chemical Safety Assessment has not been carried out.*

*
SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· ***Relevant phrases***
H220 Extremely flammable gas.
H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H280 Contains gas under pressure; may explode if heated.
H302 Harmful if swallowed.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.
EUH066 Repeated exposure may cause skin dryness or cracking.
· ***Classification according to Regulation (EC) No 1272/2008***
Data is based on internal technical data and technical data from suppliers.
The propellant gas is not taken into account when determining the classification of the mixture for health and the environment.
· ***Abbreviations and acronyms:***
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
ICAO: International Civil Aviation Organisation
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOC: Volatile Organic Compounds (USA, EU)
DNEL: Derived No-Effect Level (UK REACH)
PNEC: Predicted No-Effect Concentration (UK REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Gas 1A: Flammable gases – Category 1A
Aerosol 1: Aerosols – Category 1
Press. Gas (Comp.): Gases under pressure – Compressed gas
Flam. Liq. 2: Flammable liquids – Category 2
Flam. Liq. 3: Flammable liquids – Category 3
Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3
· **** Data compared to the previous version altered.***